

Fully Synthetic Passenger Car Motor Oil

Caretta Verge SP 0W-20 is the advanced synthetic energy conserving motor oil specially developed for the most modern high output gasoline and turbocharged engines in passenger cars, sport utility vehicles and light-duty trucks, operating on ethanol-containing fuels up to E85. It is formulated to help improve & retain fuel economy and protect vehicle emission system & turbocharger components while meeting the latest GM Dexos1™ demands.

Caretta Verge SP 0W-20 is based on high quality synthetic base oil in combination with a special selected additive package to reach to following properties:

- Improved protection against stochastic pre-ignition
- Improving sludge protection, piston cleanliness, turbo-charger protection, seal compatibility, wear protection
- Special friction modifiers used in this Energy conserving oil help improving & retaining fuel economy.
- Offers excellent lubrication at low temperatures and protect engine at high temperatures.
- Superior volatility characteristics reduce oil consumption and hydro-carbon pollution (VOCs).
- Advanced additive chemistry helps in emission system durability.
- Compatible with ethanol-containing fuels up to E85.

Caretta Verge 0W-20 meets the following performance criteria:

API SP	API SN	API SN + RC	ILSAC GF-6A
Dexos1™ Gen 3	Ford WSS-M2C960-A1	GM 4718M	Chrysler MS-6395

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-20
Density @15°C	kg/m³	ASTM D4052	845.9
Kin. Viscosity @40°C	mm²/s	ASTM D7042	41.9
Kin. Viscosity @100°C	mm²/s	ASTM D7042	8.0
Viscosity Index		ASTM D2270	167
Viscosity CCS @-30°C	cP	ASTM D5293	5440
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.1