

High Performance Engine Oil

Caretta Verge CFP 0W-30 is a very high performance fuel saving oil based on Synthetic technology for use in the very latest gasoline and diesel engines of passenger cars equipped with exhaust particle filters. Designed to meet the requirements for the new Ford M2C950-A specification for diesel engines. Also suitable for the latest Peugeot/Citroën vehicles that require PSA B71 2312.

Caretta Verge CFP 0W-30 is formulated with high quality synthetic base stocks in combination with special selected additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Excellent high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- Excellent dispersancy and detergency level.
- Very high viscosity index.

Caretta Verge CFP 0W-30 exceeds the following performance criteria:

API SP
ACEA C2

PSA B71 2302
Ford M2C950-A

PSA B71 2312
VWC 53035

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15°C	kg/m ³	ASTM D4052	846.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	50
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.5
Viscosity Index		ASTM D2270	178
Viscosity CCS @-35°C	cP	ASTM D5293	6000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	10.4
Sulphated Ash	%Wt	ASTM D874	0.79